

Package dimensions

Series		Model	Standard packaging (road transport)						Reinforced packaging (marine transport)					
			Package dimensions (mm)			Package/s dimensions (mm)			Package dimensions (mm)			Package/s dimensions (mm)		
			Length	Width	Height	Length	Width	Height	Length	Width	Height	Length	Width	Height
R-290	COMMERCIAL MONOBLOCKS	CV-NPD-1	1240	650	1065	-	-	-	1240	650	1065	-	-	-
		CV-NPD-2	1240	800	1065	-	-	-	1240	800	1065	-	-	-
		CV-NPD-3	1240	1000	1065	-	-	-	1240	1000	1065	-	-	-
		CR-NPD-1	1300	830	1055	-	-	-	1300	830	1055	-	-	-
		CR-NPD-2	1380	1130	1055	-	-	-	1380	1130	1055	-	-	-
		CR-NPD-3	1380	1380	1055	-	-	-	1380	1380	1055	-	-	-
		CV-LD-0	790	520	995	-	-	-	790	520	995	-	-	-
		CV-LD-1	1090	520	1225	-	-	-	1090	520	1225	-	-	-
		CV-LD-2	1090	740	1265	-	-	-	1090	740	1265	-	-	-
		CR-ND-0	960	725	705	-	-	-	960	725	705	-	-	-
		CR-ND-1	990	960	845	-	-	-	990	960	845	-	-	-
		CR-ND-2	990	960	845	-	-	-	990	960	845	-	-	-
	CP-ND-0/1	1050	925	600	-	-	-	1140	1010	710	-	-	-	
	WATERLOO SYSTEM	DM-ND-0	1090	510	615	-	-	-	1090	510	615	-	-	-
		DM-ND-1	1340	540	765	-	-	-	1340	540	765	-	-	-
		IB-ND-0	810	560	360	-	-	-	855	605	420	-	-	-
		IB-ND-1	810	560	360	-	-	-	855	605	420	-	-	-
		IB-ND-2	1160	560	360	-	-	-	1205	605	420	-	-	-
		IB-ND-3	1860	650	360	-	-	-	1900	695	420	-	-	-
		CC-ND/SD-1	1690	610	750	-	-	-	1735	655	1040	-	-	-
		CC-ND/SD-2	1990	610	750	-	-	-	2035	655	1040	-	-	-
		WF-SD-6	1720	610	970	-	-	-	1770	660	1030	-	-	-
		WF-SD-7	1820	710	1250	-	-	-	1865	755	1310	-	-	-
		CWF-0/1	1290	510	755	-	-	-	1335	555	790	-	-	-
		CWF-2	1290	510	985	-	-	-	1335	555	790	-	-	-
		CWF-3	1390	590	1245	-	-	-	1440	640	1310	-	-	-
		CWF-4	1390	590	1495	-	-	-	1440	640	1520	-	-	-
		CWF-6	1820	710	1250	-	-	-	1865	755	1310	-	-	-
		CWF-8	1820	710	1500	-	-	-	1865	755	1520	-	-	-
AZL		COMMERCIAL MONOBLOCKS	CV-NN- 0	790	520	995	-	-	-	790	520	995	-	-
	CV-NN- 1		1090	520	1225	-	-	-	1090	520	1225	-	-	-
	CV-NN- 2		1090	740	1265	-	-	-	1090	740	1265	-	-	-
	CV-NN- 3		1040	855	1345	-	-	-	1040	855	1345	-	-	-
	CR-NN-0		960	725	705	-	-	-	960	725	705	-	-	-
	CR-NN-1		990	960	845	-	-	-	990	960	845	-	-	-
	CR-NN-2		990	960	845	-	-	-	990	960	845	-	-	-
	CR-NN-3		1205	1050	865	-	-	-	1205	1050	865	-	-	-
	SPLIT SYSTEMS	SF-NN-11	1340	540	1005	-	-	-	1385	585	1050	-	-	-
		SF-NN-12	1340	540	1005	-	-	-	1385	585	1050	-	-	-
		SF-NN-13	1340	540	765	1860	650	360	1385	585	810	1900	695	420
		SH-NN-1	1340	540	1005	-	-	-	1385	585	1050	-	-	-
		SH-NN-2	1340	540	1005	-	-	-	1385	585	1050	-	-	-
		SH-NN-3	1340	540	765	1860	650	360	1385	585	810	1900	695	420

Series	Model	Standard packaging (road transport)						Reinforced packaging (marine transport)						
		Package dimensions (mm)			Package/s dimensions (mm)			Package dimensions (mm)			Package/s dimensions (mm)			
		Length	Width	Height	Length	Width	Height	Length	Width	Height	Length	Width	Height	
HFC	LOW NOISE SPLIT SYSTEMS	SF-N-0/00	810	540	595	-	-	-	855	585	860	-	-	-
		SF-N-1/11	1 290	510	755	-	-	-	1 335	600	1 040	-	-	-
		SF-N-2/12	1 290	510	755	-	-	-	1 335	600	1 040	-	-	-
		SF-N-3/13	1 290	510	755	1 860	650	360	1 335	555	790	1 900	695	420
		SF-N-4/23	1 290	510	985	1 860	650	360	1 335	555	1 040	1 900	695	420
		SF-N-24	1 290	510	985	2 165	635	450	1 335	555	1 040	2 170	640	520
		SF-N-34	1 390	590	1 245	2 165	635	450	1 440	640	1 310	2 170	640	520
		SF-Q-10	1 290	510	755	1 040	710	700	1 335	555	790	1 085	755	970
		SF-Q-20	1 290	510	985	1 040	710	700	1 335	555	1 040	1 085	755	970
		SF-Q-21	1 290	510	985	1 390	710	700	1 335	555	1 040	1 435	755	970
		SF-Q-22	1 290	510	985	1 690	710	700	1 335	555	1 040	1 735	755	970
		SF-Q-32	1 390	590	1 245	1 690	710	700	1 440	640	1 310	1 735	755	970
		SF-Q-33	1 390	590	1 245	2 240	710	830	1 440	640	1 310	2 285	755	1 080
		SF-Q-34	1 390	590	1 245	2 740	710	830	1 440	640	1 310	2 785	755	1 080
		SF-Q-43	1 390	590	1 495	2 240	710	830	1 440	640	1 550	2 285	755	1 080
		SF-Q-44	1 390	590	1 495	2 740	710	830	1 440	640	1 550	2 785	755	1 080
		SF-D-11	1 290	890	1 020	-	-	-	1 335	935	1 100	-	-	-
		SF-D-12	1 290	890	1 020	-	-	-	1 335	935	1 100	-	-	-
		SF-D-13	1 290	510	755	1 910	1 040	465	1 335	555	790	1 955	1 085	510
		ASF-DG-1016 y 1018	1 290	890	1 020	-	-	-	1 335	935	1 100	-	-	-
		ASF-DG-1024 y 1034	1 290	890	1 020	-	-	-	1 335	935	1 100	-	-	-
		ASF-DG-1038	1 290	510	755	1 910	1 040	465	1 335	555	790	1 955	1 085	520
		SF-D-2/23	1 290	510	985	1 910	1 040	465	1 335	555	1 040	1 955	1 085	520
		SF-D-24	1 290	510	985	2 270	1 140	515	1 335	555	1 040	2 320	1 190	590
		SF-D-3	1 390	590	1 245	1 910	1 040	465	1 440	640	1 310	1 955	1 085	520
		SF-D-34	1 390	590	1 245	2 270	1 140	515	1 440	640	1 310	2 320	1 190	590
		SF-D-4/44	1 390	590	1 495	2 270	1 140	515	1 440	640	1 560	2 320	1 190	590
		VSF-0/00	850	660	1 020	-	-	-	895	705	1 070	-	-	-
		VSF-GY-10015	1 290	890	1 020	-	-	-	1 335	935	1 100	-	-	-
		VSF-11/VSF-GG-1014	1 290	890	1 020	-	-	-	1 335	935	1 100	-	-	-
		VSF-12/VSF-GG-1024 y 1034	1 290	890	1 020	-	-	-	1 335	935	1 100	-	-	-
		VSF-2/23	1 290	510	985	1 910	1 040	465	1 335	555	1 040	1 955	1 085	520
		VSF-GY-33108	1 390	590	1 245	1 910	1 040	465	1 440	640	1 310	1 955	1 085	520
		VSF-GG-3060	1 390	590	1 245	2 270	1 140	515	1 440	640	1 310	2 320	1 190	590
	SPLIT SYSTEMS	SH-N-0/00	810	540	765	-	-	-	855	585	860	-	-	-
		SH-N-1/11	810	540	835	-	-	-	855	585	860	-	-	-
		SH-N-2/22	1 040	540	925	-	-	-	1 205	590	940	-	-	-
		SH-N-3/33	1 240	740	685	1 860	650	360	1 285	785	720	1 900	695	420
		SH-N-4/43	1 240	740	775	1 860	650	360	1 285	785	820	1 900	695	420
		SH-N-44	1 240	740	775	2 165	635	450	1 285	785	820	2 170	640	520
		SH-Q-30	1 240	740	685	1 040	710	700	1 285	785	720	1 085	755	970
		SH-Q-40	1 240	740	775	1 040	710	700	1 285	785	820	1 085	755	970
		SH-Q-41	1 240	740	775	1 390	710	700	1 285	785	820	1 435	755	970
		SH-Q-42	1 240	740	775	1 690	710	700	1 285	785	820	1 735	755	970
		SH-Q-52	1 540	870	825	1 690	710	700	1 585	915	860	1 735	755	970
		SH-Q-53171/53215	1 540	870	825	1 690	710	700	1 585	915	860	1 735	755	970
SH-Q-53		1 540	870	825	2 240	710	830	1 585	915	860	2 285	755	1 080	
SH-Q-54		1 540	870	825	2 740	710	830	1 585	915	860	2 785	755	1 080	
SH-D-1/11		920	840	1 015	-	-	-	965	925	1 100	-	-	-	
SH-DG-2014 a 2018		1 040	920	1 015	-	-	-	1 085	965	1 380	-	-	-	
SH-DG-2024		1 040	920	1 300	-	-	-	1 085	965	1 380	-	-	-	
SH-D-22		1 040	920	1 300	-	-	-	1 085	965	1 380	-	-	-	
SH-D-3		1 240	1 150	1 300	-	-	-	1 285	1 195	1 380	-	-	-	
SH-D-33		1 240	740	685	1 910	1 040	465	1 285	785	720	1 955	1 085	520	
SH-D-4/43		1 240	740	775	1 910	1 040	465	1 285	785	820	1 955	1 085	520	
SH-D-44		1 240	740	775	2 270	1 140	515	1 285	785	820	2 320	1 190	590	
CONDENSING UNITS		DF - 0	810	540	595	-	-	-	855	585	640	-	-	-
		DF - 1	1 290	510	755	-	-	-	1 335	555	790	-	-	-
		DF - 2	1 290	510	985	-	-	-	1 335	555	1 040	-	-	-
		DF - 3	1 390	590	1 245	-	-	-	1 440	640	1 310	-	-	-
		DH - 0	810	540	525	-	-	-	855	585	640	-	-	-
		DH - 1	810	540	595	-	-	-	855	585	640	-	-	-
	DH - 2	1 040	540	685	-	-	-	1 085	585	720	-	-	-	
	DH - 3	1 240	740	685	-	-	-	1 285	785	720	-	-	-	
	DH - 4	1 240	740	775	-	-	-	1 285	785	820	-	-	-	
DH - 5	1 540	870	825	-	-	-	1 585	915	860	-	-	-		
WATERLOOP SYSTEM	DM - 0	600	500	380	-	-	-	640	540	440	-	-	-	
	DM - 1	1 000	420	680	-	-	-	1 040	460	740	-	-	-	
	DM - 2	1 170	450	760	-	-	-	1 210	490	820	-	-	-	