

Package dimensions

Series	Model	Standard packaging (road transport)						Reinforced packaging (marine transport)						
		Package dimensions (mm)			Package/s dimensions (mm)			Package dimensions (mm)			Package/s dimensions (mm)			
		Length	Width	Height	Length	Width	Height	Length	Width	Height	Length	Width	Height	
Industrial monoblocks	CH - 1	1 590	1 400	1 180	-	-	-	1 630	1 440	1 240	-	-	-	
	CH - 2	1 590	1 400	1 390	-	-	-	1 630	1 440	1 450	-	-	-	
	CH - 3	1 750	2 120	1 390	-	-	-	1 790	2 160	1 360	-	-	-	
	CH - 4	1 750	2 120	1 550	-	-	-	1 790	2 160	1 610	-	-	-	
	CH - 5	2 350	2 350	1 361	-	-	-	2 350	2 350	1 361	-	-	-	
Evaporator units and air coolers	Slim type	JB - 0	660	510	290	-	-	-	700	550	350	-	-	-
		JB - 1	740	521	340	-	-	-	780	561	400	-	-	-
		JB - 2	1 090	521	340	-	-	-	1 130	561	400	-	-	-
		JB - 3	1 790	595	340	-	-	-	1 830	635	400	-	-	-
		JB - 4	2 165	635	400	-	-	-	2 205	675	460	-	-	-
	Double flow	JD - 1	740	910	410	-	-	-	780	950	470	-	-	-
		JD - 2	1 090	910	410	-	-	-	1 130	950	470	-	-	-
		JD - 3	1 790	910	410	-	-	-	1 830	950	470	-	-	-
		JD - 4	2 190	1 000	460	-	-	-	2 230	1 040	520	-	-	-
		JD - 5	2 190	1 050	460	-	-	-	2 230	1 090	520	-	-	-
	Industrial double flow	KD - 1	1 600	1 340	810	-	-	-	1 640	1 380	870	-	-	-
		KD - 2	2 000	1 340	810	-	-	-	2 040	1 380	870	-	-	-
		KD - 3	2 500	1 340	810	-	-	-	2 540	1 380	870	-	-	-
	Cubic type	KC - 01	920	650	736	-	-	-	960	690	796	-	-	-
		JC - 1 / KC - 11	1 270	650	736	-	-	-	1 310	690	796	-	-	-
		JC - 2 / KC - 22	1 570	650	736	-	-	-	1 610	690	796	-	-	-
		JC - 3 / KC - 32 - 33	1 970	600	736	-	-	-	2 010	690	796	-	-	-
	Industrial cubic type	KC - 44	2 650	600	836	-	-	-	2 690	690	896	-	-	-
		KH - 11	1 400	750	946	-	-	-	1 440	790	1 006	-	-	-
		KH - 21	1 400	750	1 200	-	-	-	1 440	790	1 260	-	-	-
		KH - 12	2 150	750	946	-	-	-	2 190	790	1 006	-	-	-
		KH - 22	2 150	750	1 200	-	-	-	2 190	790	1 260	-	-	-
		KH - 13	2 900	750	946	-	-	-	2 940	790	1 006	-	-	-
		KH - 23	2 900	750	1 200	-	-	-	2 940	790	1 260	-	-	-
		KH - 14	3 650	750	946	-	-	-	3 690	790	1 006	-	-	-
		KH - 24	3 650	750	1 200	-	-	-	3 690	790	1 260	-	-	-
		KJ - 12	3 030	980	990	-	-	-	3 070	1 020	1 050	-	-	-
		KJ - 13	4 230	980	990	-	-	-	4 270	1 020	1 050	-	-	-
KJ - 14		5 430	980	990	-	-	-	5 470	1 020	1 050	-	-	-	
KJ - 22		3 830	1 070	1 290	-	-	-	3 870	1 110	1 350	-	-	-	
KJ - 23		5 430	1 070	1 290	-	-	-	5 470	1 110	1 350	-	-	-	
KJ - 24	7 030	1 070	1 290	-	-	-	7 070	1 110	1 350	-	-	-		
Deep-freezing	KV - 31	1 425	825	1 870	1 155	825	850	1 465	865	1 930	1 195	865	910	
	KV - 3256	2 175	825	1 870	1 930	825	850	2 215	865	1 930	1 970	865	910	
	KV - 3263	2 935	825	1 870	2 665	825	850	2 975	865	1 930	2 705	865	910	
	KV - 33	3 675	825	1 870	3 485	825	850	3 715	865	1 930	3 525	865	910	
	KV - 41	1 425	825	2 120	1 155	825	850	1 465	865	2 180	1 195	865	910	
	KV - 42	2 175	825	2 120	1 930	825	850	2 215	865	2 180	1 970	865	910	
	KV - 43	2 935	825	2 120	2 665	825	850	2 975	865	2 180	2 705	865	910	
	KV - 44	3 675	825	2 120	3 485	825	850	3 715	865	2 180	3 525	865	910	
Condensing units and chillers	intarbox	DH - 0	700	460	475	-	-	-	740	500	535	-	-	-
		DH - 1	738	495	556	-	-	-	778	535	616	-	-	-
		DH - 2	973	495	640	-	-	-	1 013	535	700	-	-	-
		DH - 3	1 015	640	655	-	-	-	1 055	680	715	-	-	-
		DH - 4	1 145	670	725	-	-	-	1 185	710	785	-	-	-
	Siglus	DF / WF - 5	1 475	815	796	-	-	-	1 515	855	856	-	-	-
		DF / WF - 0	730	365	562	-	-	-	770	405	622	-	-	-
		DF / WF - 1	1 150	430	720	-	-	-	1 190	470	780	-	-	-
		DF / WF - 2	1 200	466	970	-	-	-	1 240	506	1 030	-	-	-
		DF / WF - 3	1 310	547	1 240	-	-	-	1 350	587	1 300	-	-	-
		DF / WF - 4	1 310	547	1 490	-	-	-	1 350	587	1 550	-	-	-
		DF / WF - 6	1 680	840	650	-	-	-	1 720	580	710	-	-	-
		DF / WF - 7	1 680	540	970	-	-	-	1 720	580	1 030	-	-	-
	intarCUBE	DF / WF - 8	1 800	660	1 260	-	-	-	1 840	700	1 320	-	-	-
		DV / WV - 5	1 800	660	1 510	-	-	-	1 840	700	1 570	-	-	-
		DV / WV - 6	1 304	790	1 674	-	-	-	1 344	830	1 734	-	-	-
		DV / WV - 7	1 304	900	2 074	-	-	-	1 344	940	2 134	-	-	-
DV / WV - 8		1 820	900	1 980	-	-	-	1 860	940	2 040	-	-	-	
WT	WT - 1	2 310	900	2 190	-	-	-	2 350	940	2 250	-	-	-	
	WT - 2	1 650	1 180	2 297	-	-	-	1 690	1 220	2 357	-	-	-	
		2 376	1 180	2 297	-	-	-	2 416	1 220	2 357	-	-	-	

Series	Model	Standard packaging (road transport)						Reinforced packaging (marine transport)					
		Package dimensions (mm)			Package/s dimensions (mm)			Package dimensions (mm)			Package/s dimensions (mm)		
		Length	Width	Height	Length	Width	Height	Length	Width	Height	Length	Width	Height
Condensing units and chillers interWatt	DW / WW - 1	1 805	2 296	2 500	-	-	-	1 805	2 296	2 415	-	-	-
	DW / WW - 2	3 290	2 315	2 500	-	-	-	3 290	2 315	2 450	-	-	-
	DW / WW - 3	4 735	2 315	2 500	-	-	-	4 735	2 315	2 450	-	-	-
	DW / WW - 4	6 233	2 315	2 500	-	-	-	6 233	2 315	2 450	-	-	-
	DW / WW - 5	7 710	2 315	2 500	-	-	-	7 710	2 315	2 450	-	-	-
IntarSANIT	TCH - 1	1 560	1 030	650	-	-	-	1 600	1 070	710	-	-	-
	TPD - 3	1 700	950	600	-	-	-	1 740	990	660	-	-	-
	TPD - 6	1 700	1 680	600	-	-	-	1 740	1 720	660	-	-	-
CO ₂ systems	ET - 1	2 550	1 150	2 300	-	-	-	2 610	1 210	2 360	-	-	-
	ET - 2	3 800	1 150	2 300	-	-	-	3 860	1 210	2 360	-	-	-
	EK - 1	3 350	1 150	2 060	-	-	-	3 410	1 210	2 120	-	-	-
	EK - 2	4 350	1 150	2 060	-	-	-	4 410	1 210	2 120	-	-	-
	EW - 1	1 805	2 296	2 415	-	-	-	1 805	2 296	2 415	-	-	-
	EW - 2	3 290	2 315	2 450	-	-	-	3 290	2 315	2 450	-	-	-
	EW - 3	4 735	2 315	2 450	-	-	-	4 735	2 315	2 450	-	-	-
Waterloop system	EW - 4	6 233	2 315	2 450	-	-	-	6 233	2 315	2 450	-	-	-
	CC - 1	1 590	600	650	-	-	-	1 630	640	710	-	-	-
	CC - 2	1 890	600	680	-	-	-	1 930	640	740	-	-	-
	DM - 0	600	500	380	-	-	-	640	540	440	-	-	-
	DM - 1	1 000	420	680	-	-	-	1 040	460	740	-	-	-
	DM - 2	1 170	450	760	-	-	-	1 210	490	820	-	-	-
	CWF - 0 / 1	1 190	440	720	-	-	-	1 230	480	780	-	-	-
	CWF - 2	1 220	480	970	-	-	-	1 260	520	1 030	-	-	-
	CWF - 3	1 310	550	1 250	-	-	-	1 350	590	1 310	-	-	-
	CWF - 4	1 340	580	1 500	-	-	-	1 380	620	1 560	-	-	-
	CWF - 6	1 900	580	1 250	-	-	-	1 940	620	1 310	-	-	-
Ammolite	CWF - 8	1 900	580	1 500	-	-	-	1 940	620	1 560	-	-	-
	WW - MPM - 2	3 520	2 200	2 500	-	-	-	3 560	2 240	2 375	-	-	-
	WW - MPM - 3	4 980	2 200	2 500	-	-	-	5 020	2 240	2 375	-	-	-
	WW - MPM - 4	6 480	2 200	2 500	-	-	-	6 520	2 240	2 375	-	-	-
	WW - MPM - 5	7 960	2 200	2 500	-	-	-	8 000	2 240	2 375	-	-	-
WW - MPM - 7	10 920	2 200	2 500	-	-	-	10 960	2 240	2 375	-	-	-	

Sales terms

Except in case of agreement with INTARCON, the following general sales terms prevail:

Price

The prices indicated in this list, except for typographical errors, are retail prices with cash payment, do not include VAT or indirect taxes, and will remain in force during the period of validity of this catalogue or until a new edition.

Installation

The buyer admits that INTARCON's products are capital goods for integration in a refrigeration installation. To that effect, the buyer assumes obedience to any applicable law and to guarantee the quality of the installation, which, in any case, is to be done by an authorised installer.

Orders

The orders are to be placed in writing and to be confirmed by the seller through a pro forma invoice indicating the shipping date. The seller reserves the right to refuse an order. Once manufacturing has started, no cancellations will be accepted.

Packaging

Prices include standard packaging for road transport, not suitable for overseas transport.

Delivery

The delivery of INTARCON goods is according to FCA INTARCON (PI Los Santos, 14900 Lucena, Córdoba - Spain) according to Incoterms 2020 of the ICC. The only accepted delivery claims are those received in written on the delivering note within 24 hours from the delivery.

Refunds

No refunds will be accepted without prior authorisation from the manufacturer and, in any case, an amount no less than 10 % of the purchasing price will be deducted as a return cost.

Technical-features

The information and features in this catalogue are given as an indication, technical data can be changed with no prior communication, and should be confirmed when placing an order.

Warranty

The seller guarantees the product against any manufacturing default for 12 months from delivering date.

During the warranty period the manufacturer will cover the repair of the product in its facilities, the replacement of the product or the supply of spare parts for defective components, which is less burdensome and technically feasible. The cost and taxes on the refrigerant are expressly excluded from the warranty coverage when it has not been supplied by the manufacturer in hermetically sealed appliances. The warranty does not cover on-site labour for the replacement of the product or spare parts, nor the indirect damages or consequential losses that may be attributed to the malfunction of the product. Specifically, the manufacturer may not be responsible for the Tax on Fluorinated Gases stipulated in Law 16/2013, emitted into the atmosphere as a result of a leakage of a refrigeration unit subject to a tightness and resistance test by the refrigeration installer and a periodic leak control according to Regulations 517-2014 on F-Gas and Safety for Refrigeration Installations.

Payment

Unless agreement with the manufacturer, the payment of the invoices will be in cash. The seller of the goods reserves the right to block delivery of the orders in the case that any risk in payment is perceived.

Lawsuits

INTARCON's product trade is ruled by Spanish laws. Any conflict or argument is to be submitted to the judgment of the Córdoba Chamber of Commerce. In case of disagreement, both parties will relinquish to any jurisdiction to which may pertain and they will submit to the Court of Lucena (Córdoba) Spain.